



INDOOR UNIT LINE UP



CEILING MOUNTED CASSETTE
(ROUND FLOW WITH SENSING)



CEILING MOUNTED CASSETTE
(ROUND FLOW)




CEILING MOUNTED CASSETTE
(COMPACT MULTI FLOW)



CEILING MOUNTED CASSETTE
(DOUBLE FLOW) TYPE



CEILING MOUNTED CASSETTE
CORNER



SLIM CEILING MOUNTED DUCT



SLIM CEILING MOUNTED DUCT
TYPE (COMPACT SERIES)



CEILING MOUNTED DUCT



MIDDLE STATIC PRESSURE
CEILING MOUNTED DUCT



WALL MOUNTED



CEILING SUSPENDED




4-WAY FLOW CEILING
SUSPENDED



FLOOR STANDING



FLOOR STANDING DUCT





CONCEALED FLOOR STANDING

RESIDENTIAL UNIT


WALL MOUNTED TYPE



SLIM CEILING MOUNTED DUCT TYPE



BP Units for connection to residential indoor units



OUTDOOR UNIT



MODEL		RXMQ4AVE	RXMQ5AVE	RXMQ6AVE	RXMQ8AY1	RXMQ9AY1	
Power supply		1-phase, 220-230 V/220 V, 50/60 Hz			3-phase, 380-415 V, 50 Hz		
Cooling capacity		kcal/h	9,600	12,000	13,800	19,300	
		Btu/h	38,200	47,800	54,600	76,400	81,900
		kW	11.2	14.0	16.0	22.4	24.0
Power consumption	Cooling	kW	2.88	3.93	4.14	5.94	6.88
Capacity control		%	24 to 100	16 to 100	20 to 100		
Casing colour		Ivory white (5Y7.5/1)					
Compressor	Type	Hermetically sealed swing type			Hermetically sealed scroll type		
	Motor output	kW	1.92	3.0	3.5	3.8	4.8
Airflow rate		m ³ /min	76		106		
Dimensions (H×W×D)		mm	990×940×320		1,345×900×320		
Machine weight		kg	71	80	102	131	
Sound level (Cooling)		dB(A)	52	53	55	57	
Operation range		Cooling °CDB	-5 to 46				
Refrigerant	Type	R-410A					
	Charge	kg	2.9	3.4	3.6	5.8	
Piping connections	Liquid	mm	φ9.5 (Flare)			φ9.5 (Brazing)	
	Gas	mm	φ15.9 (Flare)		φ19.1 (Flare)	φ19.1 (Brazing)	φ22.2 (Brazing)